

## WORLD INTELLECTUAL PROPERTY ORGANI International Bureau



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

WO 91/19227 (51) International Patent Classification 5: (11) International Publication Number: A1 12 December 1991 (12.12.91) (43) International Publication Date: G03F 7/023, 7/105 (74) Agent: BELCHER, Simon, James; Urquhart-Dykes & PCT/GB91/00858 (21) International Application Number: Lord, Tower House, Merrion Way, Leeds, W. Yorkshire LS2 8PA (GB). 30 May 1991 (30.05.91) (22) International Filing Date: (81) Designated States: AT (European patent), BE (European patent), CH (European patent), DE (European patent), (30) Priority data: 30 May 1990 (30.05.90) GB DK (European patent), ES (European patent), FI, FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, LU (European patent), NL (European patent), NO, SE (European patent) 9012021.3 (71) Applicant (for all designated States except US): HORSELL PLC [GB/GB]; Nepshaw Lane South, Gildersome, Morley, Leeds LS27 7JQ (GB). tent), US. (72) Inventors; and (75) Inventors/Applicants (for US only): ADEBAYO, Adelaide, **Published** Titilayo [NG/GB]; 4 Lorenzo Street, London WC1X 9DJ (GB). POWER, Gerald, Auguotine [GB/GB]; 8 Squires Court, Binfield Road, Stockwell, London SW4 6DT (GB). JOLLIFFE, Barry [GB/GB]; 31 Northern Lane, Hough Green, Widnes, Cheshire WA8 9PK (GB). With international search report.

(54) Title: LIGHT SENSITIVE MATERIALS FOR LITHOGRAPHIC PLATES

#### (57) Abstract

A method of producing a dye-containing positive working light sensitive material comprising reacting together a phenol or substituted phenol, formaldehyde and a dye capable of co-condensing with the formaldehyde and phenol or substituted phenol and then reacting the product with a quinone diazide. The material can be used as a coating for a lithographic printing plate, and can be applied directly to plates which have been anodised using sulphuric acid, without absorption of dye into the plate.

### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	Fi	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BP	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	iτ	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic	SE	Sweden
CH	Switzerland		of Korea	SN	Senegal
CI	Côte d'Ivoire	KR	Republic of Korea	SU	Soviet Union
CM	Cameroon	LI	Liechtenstein	TD	Chad
cs	Czechoslovakia	LK	Sri Lanka	TG	Togo
DE	Germany	LU	Luxembourg	US	United States of America
DK	Denmark	MC	Monaco		



10

15

20

25

30

35

## LIGHT SENSITIVE MATERIALS FOR LITHOGRAPHIC PLATES

The invention relates to positive working light sensitive materials which can be used in the production of lithographic printing plates.

Light sensitive lithographic plates are produced by applying a light sensitive coating to a suitable support for example a plate of anodised aluminium. When the plate is exposed by light reaction in the coating results in the image areas having a different solubility from the non-image areas. Development with a suitable solvent can then selectively dissolve away the more soluble of the areas. A positive working plate is one in which the exposed, light-struck, areas are more soluble than the unexposed areas.

One system which is frequently used to provide a positive working light-sensitive material is a mixture of a quinone diazide with a novolak resin. On exposure light converts the quinone diazide to an indene carboxylic acid which is soluble in and developable by an alkaline aqueous developer of about pH 11.

Dyes are often included in the light sensitive materials so that the image can be visibly inspected. The dyes used are of two kinds, those which retain the same colour throughout the exposure and development process and those which change colour when exposed. In the case of the former the image is distinguished from the non-image when dye is selectively removed during development. In the latter case a change in colour occurs on irradiation so that the non-image area is distinguished from the image area. The colour change results from the use of a pH-indicating dye which, in the case where a quinone diazide is used as the light sensitive material, changes colour due to

10

15

20

25

30


35

increased acidity caused as the diazide converts to carboxylic acid groups. For example GB 1347759 describes a positive working material which exhibits a colour change upon exposure to light and which comprises in admixture a diazonium salt, a novolak resin and a hydroxy substituted aryl azo compound which undergoes a colour change in the presence of the acid produced by the diazonium salt on exposure to light.

Often the coating on a positive working lithoplate will be formulated to contain both a permanent dye and a pH indicating dye. In this way there is both a constant colour to the coating and a colour change on exposure.

Dye containing systems suffer from the drawback that they are not generally suitable for use directly on a freshly sulphuric acid anodised substrate. is because the dye is absorbed by the substrate and can not be washed off during development. necessary for the plate to undergo a post anodic treatment before the coating of light sensitive material and dye is applied so as to pacify the substrate and prevent absorption of the dye on it. Various different post anodic treatments are commonly employed in the industry to achieve this, for example silicating, phosphating and treatment with polycarboxylic acid. These treatments have the effect of sealing the surface of the plate to prevent absorption of dye. Unfortunately the use of a post anodic treatment has the effect of reducing the press durability (run length) of a plate and also involves additional cost because of the extra manufacturing step involved.

There is thus a need for dye-containing positive working light sensitive materials for use as coatings for lithographic plates which can be applied directly



15

20

25

30

35

to freshly sulphuric acid anodised plates without absorption of dye into the plate.

In accordance with a first embodiment of the invention there is provided a method of producing a dye-containing positive working light sensitive material comprising reacting a novolak resin with a dye capable of reacting with phenolic -OH groups on the novolak and a quinone-diazide.

In accordance with a second embodiment of the invention there is provided a method of producing a dye-containing positive working light sensitive material comprising reacting together a phenol or substituted phenol, a reactive dye and formaldehyde and then reacting the product with a quinone diazide.

The present invention thus provides two methods of producing light sensitive materials in which a dye is incorporated directly in the molecule of light sensitive novolak rather than being present as a separate component in a light sensitive composition.

When light sensitive materials produced according to either of these methods are used as coatings directly on freshly sulphuric acid anodised lithographic plates and subsequently irradiated and developed the background (non-image) areas are not dye stained. It is thought that the extra bulk and large molecular weight of the dye which is bound to the novolak prevents it from being absorbed.

In the first embodiment the dye-containing novolak is prepared by reacting a pre-prepared novolak resin with both a dye and a quinone diazide. For the necessary reaction to occur the dye must be one which is capable of reacting with phenolic -OH groups on the novolak. The quinone diazide reacts with other phenolic -OH groups on the novolak. The dye may be a permanent dye or a pH-indicating dye provided it can undergo the necessary reaction.



WO 91/19227

5

10

15

20

25

30

35

Examples of dyes which have been found to work particularly well in this first method are permanent dyes such as those which contain a cyanuric chloride or sulphonyl chloride group. Specific examples are the commercially available Procion dyes such as Procion blue MX-G available from ICI.


Novolak resins which may be employed in this embodiment include those commonly used to prepare positive working light sensitive materials. Such novolaks are formed by condensing phenol or substituted phenol with formaldehyde. Specific examples of such novolaks include those based on cresol formaldehyde, such as Bakelite.

In the second embodiment the dye-containing light sensitive material is prepared by reacting a dye into the polymer chain at the same time as the novolak is formed by reaction of a phenol or substituted phenol with formaldehyde. In this case the dye reacts into the molecule in a different way by co-condensing with the formaldehyde and phenol or substituted phenol. The co-condensed polymer is then reacted with a quinone diazide which reacts with phenolic -OHs of the polymer.

This embodiment may be used to produce light sensitive materials containing either permanent or pH indicating dyes. Thus, the permanent dyes mentioned above may be used. It is, however, particularly suitable for use with pH indicating dyes, for example phthaleins or sulphophthaleins. A particular example of a sulphophthalein dye which may be employed in this embodiment is Phenol Red.

Phenol or substituted phenol compounds which may be employed in this embodiment include those commonly used to produce novolak resins.

The quinone diazide used as the light sensitive component of the material includes those



conventionally employed in light sensitive coatings for lithoplates, for example a napthaquinone diazide sulphonyl chloride. Specific examples include 2-diazo-1-naphthol-4-sulphonyl chloride and 2-diazo-1-naphthol-5-sulphonyl chloride.

The present invention includes positive working light sensitive material produced by the methods of the first and second embodiments of the invention. In general the invention consists of positive working light sensitive material comprising a novolak resin which is functionalised with both a dye and a quinone diazide.

The reaction schemes involved in the production of the positive working light sensitive materials by the methods of the first and second embodiments of the invention are illustrated below.

## REACTION SCHEME - ROUTE |

where 
$$R_3 = a \, dye$$

$$CH_2 \longrightarrow CH_2 \longrightarrow CH_2$$

$$SO_2CE$$

$$N_2 \longrightarrow CH_2$$

$$N_3 \longrightarrow CH_2 \longrightarrow CH_3$$

$$CH_2 \longrightarrow CH_2 \longrightarrow CH_2$$

$$CH_2 \longrightarrow CH_2$$

## SUBSTITUTE SHEET

# REACTION SCHEME - ROUTE 2

OH + HCHO 
$$H^+$$
 OH  $CH_2OH$ 

$$CH_2OH$$

## SUBSTITUTE SHEET



The invention is illustrated by the following examples.

### Example 1

Production of a positive working light sensitive material by reaction of a novolak resin with a dye and a napthaquinone-diazide sulphonyl chloride.

10

15

20

25


30

3-5

5

5.00g of Bakelite LB744, a novolac resin based on cresol formaldehyde, was dissolved in 16g of 2-methoxy ethanol with stirring. To this mixture was added 0.82g of sodium hydrogen carbonate, 5.00g water, 0.85g Procion blue MX-G (available from ICI) and 1.32g of 2-diazo-1-napthol-4-sulphonyl chloride (DNSC). This reaction mixture was stirred for two hours at 20°C during which the Procion blue dye reacted with some of the phenolic -OH groups of the novolak while the DNSC reacted with some of the other available phenolic -OH groups, to produce a resin functionalised with both dye and the photosensitising napthoquinone diazide. The mildly alkali sodium hydrogen carbonate was present to counter the acid HCl produced during the reaction. Product was recovered by precipitation into acidified water, followed by filtration, washing and drying.

The light sensitive product obtained was then used to produce a positive working lithographic plate. The product was dissolved in 2-methoxy ethanol at a concentration of 20% w/w and then coated onto an aluminium sheet which had been freshly anodised with sulphuric acid. After drying the coated sheet was exposed with UV radiation. This caused a reaction in the light sensitive napthoquinone diazide functional groups of the exposed background areas which rendered



them more soluble than the image areas. Thus, subsequent development in aqueous alkaline solution selectively dissolved away the background to reveal a coloured image. There was no dye staining of the background (non-image areas).

The Procion blue provides a permanent dye colour which does not change exposure.

### Example 2

10

25

Production of a polymeric dye by a cocondensation reaction of a phenolic compound and a dye with formaldehyde.

15 37.6g of Phenol Red, 68.0g of phenol, 56.7g of formaldehyde (37% aqueous solution), 20.0g of water and 3.0g of oxalic acid were mixed together and the mixture refluxed for three hours. The water was then removed under vacuum until a sample formed a brittle solid on cooling.

In order to obtain a pH indicator operating in a most suitable range (pH 2.5 to 5.0) bromination of the phenol/Phenol Red/formaldehyde condensate obtained above was carried out as follows.

To 10g of the product obtained above in 100g of sodium hydroxide there was added a solution of bromine in aqueous solution bromide until a dark red solid separated which was filtered off and dried.


A coatable composition was prepared from the 30 following ingredients:

	Bakelite LB744/naphthoquinone		
	diazide sulphonate	16%	w/v
	Brominated phenol/Phenol Red/		
35	formaldehyde condensate	4%	w/v
	2-methoxy ethanol	80%	w/v






The composition was bar coated onto a freshly sulphuric acid anodised sheet of aluminium and imagewise exposed to active radiation. The composition showed a distinct colour change from blue to yellow. The plate was then developed in an aqueous alkaline solution which removed the yellow exposed non-image areas of the coating to reveal the anodic film which showed no staining.



#### CLAIMS:

25

- A method of producing a dye-containing positive working light sensitive material comprising reacting a novolak resin with a dye capable of reacting with phenolic -OH groups on the novolak and a quinone diazide.
- 2. A method of producing a dye-containing positive working light sensitive material comprising reacting together a phenol or substituted phenol, formaldehyde and a dye capable of co-condensing with the formaldehyde and phenol or substituted phenol and then reacting the product with a quinone diazide.
  - 3. A method as claimed in claim 2 in which the dye is a pH-indicating dye.
- 20 4. A method as claimed in claim 3 in which the dye is a phthalein or sulphophthalein dye.
  - 5. A method as claimed in claim 4 in which the dye is Phenol Red.
  - 6. A method as claimed in claim 1 or claim 2 in which the dye is a permanent dye.
- A method as claimed in claim 6 in which the dye
   contains a cyanuric chloride or sulphonyl chloride group.
  - 8. A method as claimed in claim 7 in which the dye is a Procion dye.
  - 9. A method as claimed in any one of claims 1 to 8



35

in which the quinone diazide is a napthaquinone diazide sulphonyl chloride.

- 10. A method as claimed in claim 9 in which the quinone diazide is 2-diazo-1-naphthol-4-sulphonyl chloride or 2-diazo-1-naphthol-5-sulphonyl chloride.
  - 11. A positive working light sensitive material produced by the method of any one of claims 1 to 10.
- 12. A positive working light sensitive material comprising a novolak resin which is functionalised with both a dye and a quinone diazide.
- 13. A material as claimed in claim 12 in which the quinone diazide functionality has been provided by reaction with napthaquinone diazide sulphonyl chloride.
- 20 14. A material as claimed in claim 13 in which the quinone diazide functionality has been provided by reaction with 2-diazo-1-naphthol-4-sulphonyl chloride or 2-diazo-1-naphthol-5-sulphonyl chloride.
- 25 15. A material as claimed in any one of claims 12 to 14 in which the dye functionality is pH-indicating.
- 16. A material as claimed in claim 15 in which the dye functionality has been provided by reaction with30 a phthalein or sulphophthalein dye.
  - 17. A material as claimed in claim 16 in which the dye functionality has been provided by reaction with Phenol Red.
  - 18. A material as claimed in any one of claims 12 to



14 in which the dye functionality comprises a permanent dye.

- 19. A material as claimed in claim 18 in which the dye functionality has been provided by reaction with a dye containing a cyanuric chloride or sulphonyl chloride group.
- 20. A material as claimed in claim 19 in which the dye functionality has been provided by reaction with a Procion dye.

15

20

25



	Y	MICKIANIONAL		International Appl	/GB 91/00858
I CLASSIE	CATION OF SUBJE	CT MATTER (if several classification	symbols	apply, indicate all)	
According to	o International Patent	Classification (IPC) or to both National	Classific	ation and IPC	
		G03F7/023; G03F7/10	5		
2110.0					
	SEARCHED.				
II. FIELDS	SEARCHED	Minimum Docur	nentatio	n Searched?	
		1		fication Symbols	
Classificati	on System	1		-	
Int C	1 5	G03F			
1110.0	,,,,				
		Documentation Searched other		Minimum Doggrammetina	
		Documentation Searches other to the Extent that such Document	s are In	cluded in the Fields Searched <sup>8</sup>	
		·			
					•
		TO ME DEL TALETT			
	MENTS CONSIDER	ED TO BE RELEVANT <sup>9</sup> Document, <sup>11</sup> with indication, where appro-	oriate. o	f the relevant passages 12	Relevant to Claim No.13
Category °	Citation of D	ocument, at with indication, where appro-			
l., .,	DATIDAG	SE WPI, no. 71-70002s			2-5, 11,
X,Y	DATABAS	Publications Ltd, Log	ndon.	GB	15-17
	Derwent				
	* The v	-289389 (Bokov y. et a whole abstract *			
					0_E 11
lγ	PATENT	ABSTRACTS OF JAPAN		1000	2-5, 11, 15-17
[	12	no 172 (D-862)(352)	0) 24	April 1989,	15-17
Int.Cl.  II. FIELDS SEA  Classification S  Int.Cl.  Int.Cl.  Int.Cl.  Classification S  Int.Cl.  X, Y  Y  A  Special C  "A" docur consil E filing "L" docur which cher "P" docur later  IV. CERTIFI  IV. CERTIFI	I & JP−A-	-01 006348 (KOMIKA COK	P) 1.	L January 1969,	İ
	see the	whole document			
١.	110 4 30	329488 (SMITH P.J.) 30	Dece	ember 1975	
Α	US,A,3	e whole document	500		İ
	& GR A	,1347759			
	(cited	in the application)		•	
	(5.552				
				-	
1					
1	1	•			
	1				
	al categories of cited	incuments: 10	"1	later document published after the inter	national filing date
	answert defining the	peneral state of the art which is not		or priority date and not in conflict with cited to understand the principle or the	ry underlying the
1 0	onsidered to be of part	DCDITT LEIGHTUCE	_	invention  or document of particular relevance; the cl	
1 1	ling date	oblished on or after the international	-2	cannot be considered novel of cannot be	considered to
	amment which may th	row doubts on priority claim(s) or sh the publication date of another	-	involve an inventive step  "document of particular relevance; the cl	aimed invention
l d	itation or other special	reason (as specifies)		cannot be considered to involve an inve	other such docu-
1 0	ther means	un oral disclosure, use, exhibition or		ments, such combination being obvious	to a person skilled
- Pr d	ocument published pri	or to the international filing date but	• /	in the art.  R" document member of the same patent for	ımily
L"	ater than the priority (	INC CARROL			
				Date of Mailing of this International Se	arch Report
Date of th		of the International Search		Date of talantile of this interpretational of	
ı	20 A	UGUST 1991		/ llude	A 25
				Signature of Authorized Officer	
Internatio	nal Searching Author			LUDI M.M.B.	
1	EUROF	PEAN PATENT OFFICE	- 1	CODI M.M.D.	



### ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

GB 9100858 47973 SA

This amex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20/08/91 -

Patent document cited in search report
US-A-3929488